


## Product Information

Universal module of three phase power supply monitoring BKT BPS2500, socket 1 x IEC 60309, plug 1 x IEC 60309

No. Card: PI\_B25Vg10045201A01B\_01.19

A universal module of three phase power supply monitoring extends the functionality of PDU Basic with additional monitoring and management options. Due to their small dimensions and application of 2 metre power supply cables, they allow for both vertical OU and horizontal installation.




They can be used to monitor the power supply voltage [V], actual current load [A], current power [kW], reactive power [VAR], apparent power [VA] and energy consumption [kWh]. Additional port for connecting temperature and humidity sensor provides monitoring of environmental conditions in rack cabinet.




## Standards

EN 60950-1; EN 61000-3-2; EN 61000-3-3; EN 55022; EN 55024

## Features

Index no.	B25Vg10045201A01B
Functionality	Input / phase measurement
Power plug on cable	IEC 60309 16A/400V H05VV-F 5 x 2.5 mm <sup>2</sup> , 2.0 m, black
Sockets on cable	IEC 60309 16A/400V H05VV-F 5 x 2.5 mm <sup>2</sup> , 2.0 m, black
Additional components	Lack
Ports for connecting sensor	1 x Temperature/Humidity
Maximum unit load	3x16A
Unit rated power	3x3680W
Dimensions (L x W x D) [mm]	395 x 44 x 68
Net/Gross weight [kg]	3.1/3.5
Housing	OU, black aluminium
Fixed brackets	
Brackets for BKT 4DC cabinets (must be ordered separately)	
Power plug view	

SOCKET 16A/400V  IEC 60309	RATED POWER  <b>11 kW</b>
CABLE LENGHT  <b>2.0 m</b>	WARRANTY  <b>2 YEARS</b>