

## Technical Specification

Vertical management power distribution unit BKT RPDU type D 18xIEC320 C13 + 6xIEC320 C19, plug IEC 60309

No. Card: PI\_RPDAd18c6463E2AA2B\_01.19

The power distribution unit BKT RPDU gives you complete control over your rack-mounted devices, with remote and local controls. It allows you to monitor electrical parameters: supply voltage [V], current load [A], active power consumption [W], energy meters [kWh]. It allows you to take action on an ongoing basis if the defined alarm thresholds are exceeded.

The RPDU is equipped with a number of protocols for secure communication with network infrastructures (HTTPS, SNMP v3, SysLog, SSL, SSH, Radius). The measuring accuracy is  $\pm 1\%$  for energy meters and load measurement.

Additionally, the RPDU allows the monitoring of environmental parameters in the server cabinet or server room using the connected sensors: temperature / humidity, door opening, flood or smoke.




The RPDU is equipped with an electronic control panel for viewing the current parameters.





## Standards

EN 60950-1; EN 61000-3-2; EN 61000-3-3; EN 55022; EN 55024

## Features

Index no.	RPDAd18c6463E2AA2B
Functionality	Switching and measurement each sockets
Power plug	IEC 60309 32A/400V
Cable	H05VV-F 5 x 6.0 mm <sup>2</sup> , 3.0 m, black
Sockets	18 x IEC320 C13 10A/250V 6 x IEC320 C19 16A/250V
Circuit breaker	3x32A
Additional components	Lack
Ports for connecting sensors	2 x Temperature/Humidity
Maximum unit load	3x32A
Unit rated power	3x7360W
Dimensions (L x W x D) [mm]	1850 x 56 x 52 1850 x 56 x 83.5 (with fuse housing)
Nett/Gross weight [kg]	9.0/12.0
Housing	0U, black steel
Brackets for BKT 4DC cabinets (must be ordered separately)	
Included default tool-free brackets type: L - Z	
Power plug view	

SOCKETS 10A/250V  IEC320 C13	SOCKETS 16A/250V  IEC320 C19
RATED POWER <b>22 kW</b>	CABLE LENGTH <b>3.0 m</b>
WARRANTY <b>2 YEARS</b>	