

Product Information

BKT vertical power distribution unit three phase 24xNF C61-314, plug IEC 60309, 3 x LED control light

No. Card: PI_11341B30.24-1_02.19

Power Distribution Units (PDUs) are designed for basic power distribution, designed for telecommunications cabinets.

The devices are intended for vertical installations. The housing is made of black aluminum.





M6 screws with nuts in a box with washers attached to each PDU.




Standards

EN 60950-1, EN 60669-1, EN 60669-2-1

Features

Index no.	11341B30.24-1
Power plug	IEC 60309 32A/400V
Cable	H05VV-F 5 x 6.0 mm ² , 3.0 m, black
Sockets	24 x NF C61-314 16A/250V
Additional components	3 x LED control light
Maximum unit load	3x32A
Unit rated power	3x7360 W
Dimensions (L x W x D) [mm]	1275 x 44 x 68
Net weight [kg]	3.2
Gross weight [kg]	3.7
Housing	0U, black aluminium
Fixed brackets type 44	
Brackets for BKT 4DC cabinets (set) Index: 111SA200011.3	
Brackets for BKT SRS/SSRS cabinets (must be ordered separately) Index: 111SA200018.3	
Power plug view	

SOCKETS 16A/250V  NF C61-314	RATED POWER 22 kW
CABLE LENGTH 3.0 m	WARRANTY 2 YEARS