

## Product Information

ATS Basic BKT 1U 19" 6xIEC320 C13 + 2xIEC320 C19, plug 2xIEC320 C20

No. Card: PI\_1134A4.06-2,02-6S\_01.20

BKT Elektronik has launched a product that provides redundancy and uninterrupted operation of network devices. ATS switches between power lines in no more than 16 ms for load up to 16A current, not interrupting the operation of connected devices. When there is a power cut at Input A, the ATS automatically switches to power supply from Input B.



ATS can be applied in server rooms, data centers, telecommunication and many other areas where uninterrupted power supply is a must.





## Standards

EN 60950-1, EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3

## Features

Index no.	1134A4.06-2.02-6S
Power plug	2 x IEC320 C20 16A/250V
Cable	H05VV-F 3 x 1.5 mm <sup>2</sup> , 3.0 m, black, C19/DIN49441
Sockets	6 x IEC320 C13 10A/250V 2 x IEC320 C19 16A/250V
Slot for SNMP card	Yes
Additional components	Absence
Maximum unit load	16A
Unit rated power	3680 W
Dimensions (L x W x D) [mm]	482 x 220 x 44
Net weight [kg]	3.5
Gross weight [kg]	4.8
Maximum time of switching between power sources	≤16ms
Housing	1U 19", black aluminium
Movable brackets (front/rear)	
Power plug view	
Working conditions	Temperature 0°C ÷ 40°C Humidity 10% ÷ 95%

SOCKETS 10A/250V  IEC320 C13	SOCKETS 16A/250V  IEC320 C19
RATED POWER <b>3.7 kW</b>	WARRANTY <b>2 YEARS</b>