

## Product Information

ATS Basic BKT 2U 19" 12xIEC320 C13 + 4xIEC320 C19, plug 2xIEC60309

No. Card: PI\_1134A9.12-2,04-6S\_01.20

BKT Elektronik has launched a product that provides redundancy and uninterrupted operation of network devices. ATS switches between power lines in no more than 16 ms for load up to 32A current, not interrupting the operation of connected devices. When there is a power cut at Input A, the ATS automatically switches to power supply from Input B.



ATS can be applied in server rooms, data centers, telecommunication and many other areas where uninterrupted power supply is a must.





## Standards

EN 60950-1; EN 61000-3-2; EN 61000-3-3; EN 55022; EN 55024

## Features

Index no.	1134A9.12-2,04-6S
Plug on cable	2 x IEC60309 32A/250V
Cable	H05VV-F 3 x 6.0 mm <sup>2</sup> , 2.0 m, black
Sockets	12 x IEC320 C13 10A/250V 4 x IEC320 C19 16A/250V
Slot for SNMP card	Yes
Additional components	Absence
Maximum unit load	32A
Unit rated power	7360W
Dimensions (L x W x D) [mm]	482 x 220 x 89
Net weight [kg]	5.9
Gross weight [kg]	7.6
Maximum time of switching between power sources	≤16ms
Housing	2U 19", black aluminium
Movable brackets (front/rear)	
Power plug view	

<p>SOCKETS 10A/250V</p>  <p>IEC320 C13</p>	<p>SOCKETS 16A/250V</p>  <p>IEC320 C19</p>
<p>RATED POWER</p> <p><b>7.4 kW</b></p>	<p>CABLE LENGTH</p> <p><b>2.0 m</b></p>
<p>WARRANTY</p> <p><b>2 YEARS</b></p>	