

Product Information

BKT monitoring power distribution unit BPS2000 18xIEC320 C13 + 6xIEC320 C19, plug IEC 60309

No. Card: PI_B20Vd18c644301AA1B_02.19

BKT management power distribution unit BPS2000 have been designed for telecommunications cabinets. There is a wide range of input plug standards and unit output sockets, as well as control and safety modules.

Can monitor supply voltage [V], total current-load of a unit [A], total power [kW], total consumption [kWh] and temperature with humidity in rack cabinet.





The BPS2000 have been fitted with hot-swappable measuring module with integrated electronic control panel allows operating the above-mentioned electrical parameters.





Standards

EN 60950-1; EN 61000-3-2; EN 61000-3-3; EN 55022; EN 55024

Features

Index no.	B20Vd18c644301AA1B
Power plug	IEC 60309 32A/250V
Functionality	Input/phase measurement
Cable	H05VV-F 3 x 6 mm ² , 3.0 m, black
Sockets	18 x IEC320 C13 10A/250V 6 x IEC320 C19 16A/250V
Additional components	Lack
Ports for connecting sensor	1 x Temperature/Humidity
Maximum unit load	32A
Unit rated power	7360W
Dimensions (L x W x D) [mm]	1383 x 44 x 68
Net/Gross wieght [kg]	3/3.5
Housing	0U, black aluminium
Fixed brackets	
Brackets for BKT 4DC cabinets (set) Index: 111SA200011.3	
Brackets for BKT SRS/SSRS cabinets (must be ordered separatly) Index: 111SA200018.3	
Power plug view	

SOCKETS 10A/250V  IEC320 C13	SOCKETS 16A/250V  IEC320 C19
RATED POWER 7.4 kW	CABLE LENGHT 3.0 m
WARRANTY 2 YEARS	