

## Product Information

BKT monitoring power distribution unit BPS2000 18xIEC320 C13 + 6xIEC320 C19, plug IEC 60309  
 No. Card: PI\_B20V.d18c6.45301Av2\_01.21

BPS2000 is a power distribution device that enables monitoring of electrical parameters at the input.

It has been equipped with a new BPS2000v2 control module made in the "Hot Swappable" technology, which enables supervision and control of electrical parameters with access among others via a web browser.

It allows you to control the supply voltage [V], total current load [A], power consumption [W/VA/VAR], total energy consumption [Wh/VAh] and monitoring of temperature and humidity, door opening, flooding and smoke in the server cabinet.





Communication with external management systems is possible via network/communication protocols: HTTP, SNMP, Modbus, SMTP, Telnet, IPv4/IPv6.





## Standards

EN IEC 62368-1; EN 55032; EN 55035; EN61000-3-2; EN61003-3

## Features

Index no.	B20V.d18c6.45301Av2
Functionality	Input / phase measurement
Power plug	IEC 60309 16A/400V
Cable	H05VV-F 5 x 2.5 mm <sup>2</sup> , 3.0 m, black
Sockets	18 x IEC320 C13 10A/250V 6 x IEC320 C19 16A/250V
Additional components	None
Ports for connecting sensor	1 x Temperature/Humidity
Maximum unit load	3 x 16A
Unit rated power	3 x 3680W
Dimensions (L x W x D) [mm]	1383 x 44 x 68
Net/Gross weight [kg]	3.5/4.0
Housing	0U, black aluminium
Fixed brackets type 44	
Brackets for BKT 4DC cabinets (set) Index: 111SA200011.3	
Brackets for BKT SRS/SSRS cabinets (must be ordered separatley) Index: 111SA200018.3	
Power plug view	

SOCKETS 10A/250V  IEC320 C13	SOCKETS 16A/250V  IEC320 C19
RATED POWER <b>11 kW</b>	CABLE LENGHT <b>3.0 m</b>
WARRANTY <b>2 YEARS</b>	